

EH6



Caratteristiche tecniche:

1. Elemento riscaldante PTC.
2. Doppio livello di riscaldamento.
3. Funzione ventilazione.
4. Protezione da surriscaldamento.
5. Adatto ad officine, uso residenziale, ecc.
6. Maniglia regolabile per direzionare il flusso di aria calda.
7. Colore: Rosso



Technical specifications:

1. PTC heating element.
2. Equipped with two switches for power setting.
3. Ventilation mode available.
4. Overheating protection.
5. Suitable for workshops, residential use, etc.
6. Adjustable handle to direct heat stream.
7. Colour: Red



Modello Model	Aliment. elettrica Electrical supply	Potenza di riscaldamento Heating output	Superficie m ² Heating Area m ²	Uscita aria Air output	Imballo Packing	P.N. N.W.	P.L. G.W.	Dim. Prodotto Product Dim	Dim. Imballo Packing Dim
				m ³ /h m ³ /h	pzi/cad pcs/ctn	kg kg	kg kg	mm mm	mm mm
EH6-02	220-240V 1Ph-50Hz	1000/2000 W	20	100	8	1,6/ cad	15,7	210x160x217	450x350x500
EH6-03	220-240V 1Ph-50Hz	1500/3000 W	35	150	1	2,9	3,2	210x265x290	220x290x320

GENERATORI D'ARIA CALDA A GAS GAS HEATERS



GH1



Caratteristiche tecniche:

1. Funziona con propano o butano (GPL)
2. Protezione da surriscaldamento.
3. Valvola di sicurezza per prevenire perdite di gas.
4. Ugello speciale, con notevole apporto di ossigeno, per permettere una combustione completa.
5. Accensione piezoelettrica.
6. Regolatore di pressione del gas e tubo gas (1.5 m) inclusi.
7. Certificazione gas CE.
8. Adatto all'uso in un ambiente ben ventilato.
9. Colore: Rosso



Technical specifications:

1. It works on propane and butane gas (LPG).
2. Over-heating protection.
3. Cut-off valve to avoid gas leaking.
4. Special nozzle, with strong oxygen supply allowing complete combustion.
5. Manual start with piezo ignition.
6. Gas pressure regulator & gas hose (1.5 m) included.
7. CE gas certification.
8. Suitable to be used in a well ventilated area.
9. Colour: Red



Modello Model	Aliment. elettrica Electrical supply	Potenza di riscaldamento Pressione gas Heating output	Consumo carburante Fuel consump- tion	Uscita aria Air output	Imballo Packing	P.N. N.W.	P.L. G.W.	Dim. Prodotto Product Dim	Dim. Imballo Packing Dim
				m ³ /h m ³ /h	pzi/cad pcs/ctn	kg kg	kg kg	mm mm	mm mm
GH1-15	220-240V 1Ph-50Hz	15 KW - 0,7 bar	1.09 Kg/h	320	1	3,8	4,4	380x190x305	400x225x295
GH1-30	220-240V 1Ph-50Hz	30 KW - 0,7 bar	2.18 Kg/h	650	1	6,1	6,8	475x225x360	490x265x360
GH1-50	220-240V 1Ph-50Hz	50 KW - 1,5 bar	3.63 Kg/h	872	1	6,9	7,9	580x225x360	605x250x335